



What's Inside:

- 1 Key Benefits
- 2 Reliable Network Connectivity
- 2 Better User Experience
- 3 Lower ISP Costs
- 4 BIG-IP Link Controller Platforms
- 4 More Information



Take Control of Multiple ISP Connections

Your ISP connections are your link to the outside world. Having multiple connections can increase availability and performance, but managing multiple links can be difficult.

BIG-IP® Link Controller™ puts the management of these links under your control. It monitors the performance and availability of each link and directs connections—both inbound and outbound—over the best possible link. It also improves application performance by prioritizing and optimizing traffic. BIG-IP Link Controller gives you the tools to direct traffic over the most cost-effective connections first so you can keep your ISP costs at a minimum.

The result is more effective use of multiple ISP connections for greater reliability, better performance, and lower costs.

Key benefits

Eliminate downtime caused by link and ISP failures

Monitor the health and availability of each connection to dynamically direct users around ISP outages.

Improve application performance

Route users over the best link and optimize the connection to provide the best application experience.

Control ISP costs

Aggregate inexpensive links and create policies to control your bandwidth costs.

Reliable Network Connectivity

BIG-IP Link Controller dynamically distributes traffic to ensure that your business is always connected.

Comprehensive link monitoring

With a comprehensive view into the health and throughput of links going through the gateway router, BIG-IP Link Controller provides visibility into the bandwidth and capacity of any given link.

High availability

BIG-IP Link Controller combines multiple monitors to quickly and accurately determine the health and availability of every link. If a problem is detected, traffic can be rerouted to other available links, maintaining client connectivity without incurring the costs of downtime.

Programmable link routing with iRules

Using the F5 iRules® scripting language, you can intelligently route traffic over multiple WAN links, based on TCP/IP parameters such as source IP address, destination IP address, and port. With iRules, you can define policies to distribute traffic over the best performing links based on application type, quality of service, and client types, improving application performance and user experience.

Better User Experience

BIG-IP Link Controller routes users over the best link and optimizes the connection to provide a better application experience.

Best performing link

Using round-trip time and line quality calculations, BIG-IP Link Controller tests which connection will provide the best service for each user, and then it directs the user to that link. This ensures the fastest possible service and highest quality connections.

Link capacity and throughput

You can use BIG-IP Link Controller to define and control how traffic is distributed across links based on real-time traffic flows and throughput. This increases application performance and available bandwidth while removing the risk of saturating any one link. When a link nears its capacity, traffic is shifted to less congested links, boosting overall site performance.

Integrated rate shaping

BIG-IP Link Controller gives you a powerful way to classify and prioritize application traffic on WAN links to use bandwidth more efficiently. Rate shaping enables you to define traffic and application limits, control the rate at which those resources are allowed to spike or burst, use queuing to prioritize traffic types, and define relationships where certain traffic types can borrow from other types. With quality of service (QoS) and terms of service (ToS), you can identify critical traffic or applications for special handling by upstream routers. This ensures that high-priority traffic is routed first.

BIG-IP Link Controller provides advanced link traffic distribution capabilities.

- Round robin
- Round-trip time
- Global availability
- Hops
- Static persistence
- Packet completion rate
- Topology
- User-defined QoS
- Virtual server capacity
- Dynamic ratio
- Least connections
- Random
- Packets rate
- Ratio
- Kilobytes per second

Topology-based routing

BIG-IP Link Controller can accurately determine the location of users and route traffic over the desired link based on pre-defined policies. This lets you choose the best performing link based on location, while avoiding inter-ISP routing issues that can result in high latency and poor performance.

Optimized TCP performance

TCP protocol inefficiencies can cause unnecessary chattiness. BIG-IP Link Controller leverages TCP Express™ to overcome TCP protocol inefficiencies. This gives you the ability to completely fill the pipe over long distances for lower bandwidth bills and prioritize bandwidth availability for mission-critical applications.

Compression (option)

An optional compression module enables you to compress traffic, reduce WAN link bandwidth, and remove bottlenecks for faster application delivery. Granular control of link bandwidth utilization for different connection types results in an improved client experience, with more efficient WAN link administration and improved productivity. You can configure the compression engine based on document type, traffic type, and network conditions such as round-trip time.

Lower ISP Costs

Control your ISP costs with BIG-IP Link Controller.

Bandwidth scalability

Regardless of the link type or provider, BIG-IP Link Controller can aggregate small, inexpensive lines to lower bandwidth costs and minimize the money spent on dark fiber or unused standby lines.

Link cost load balancing

BIG-IP Link Controller gives you the ability to define the cost of each connection and the billing scheme, and then it will automatically direct traffic based on your criteria. This enables you to define policies that direct traffic over the least expensive link or maximize bandwidth across different connections to eliminate bandwidth bottlenecks and minimize inefficient bandwidth.

Eliminates barriers of multi-homing with BGP

BIG-IP Link Controller eliminates deployment barriers and reduces the cost of multi-homing via Border Gateway Protocol (BGP). You can direct traffic over the best route without purchasing larger routers, coordinating with ISPs, or obtaining specialized staff and IP addressing to run BGP.

BIG-IP Link Controller Platforms

BIG-IP Link Controller is available on the BIG-IP 1600 platform or as an add-on module for integration with BIG-IP® Local Traffic Manager™ on the following platforms: BIG-IP 1600, 3600, 3900, 6900, 8900, and 11000 series. For detailed specifications, refer to the BIG-IP System Hardware datasheet.



1600 Series

More Information

Browse for these and other resources on f5.com to learn more about BIG-IP Link Controller.

Datasheet

[BIG-IP System Hardware Datasheet](#)

White paper

[Conquering Multi-Homed ISP Link Challenges](#)

Case studies

[Organon Uses BIG-IP Link Controller for ISP Load Balancing](#)

[PDXLAN 6 Cuts Monthly Bandwidth Bills, Reduces Costs by \\$12,000](#)

F5 Networks, Inc. 401 Elliott Avenue West, Seattle, WA 98119 888-882-4447 www.f5.com

F5 Networks, Inc.
Corporate Headquarters
info@f5.com

F5 Networks
Asia-Pacific
apacinfo@f5.com

F5 Networks Ltd.
Europe/Middle-East/Africa
emeainfo@f5.com

F5 Networks
Japan K.K.
f5j-info@f5.com

